

**METHOD AND APPARATUS FOR  
SUPPORTING PAGE LOCALIZATION  
MANAGEMENT IN A WEB  
PRESENTATION ARCHITECTURE**

**By:**

SUNNY K. YEE  
BRIAN JAMES DEHAMER

# **METHOD AND APPARATUS FOR SUPPORTING PAGE LOCALIZATION MANAGEMENT IN A WEB PRESENTATION ARCHITECTURE**

## **BACKGROUND OF THE RELATED ART**

[0001] This section is intended to introduce the reader to various aspects of art, which may be related to various aspects of the present invention that are described and/or claimed below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present invention. Accordingly, it should be understood that these statements are to be read in this light, and not as admissions of prior art.

[0002] Presentations and applications are continuously developing on the World Wide Web (the “Web”), which has undergone an explosive growth in recent years. Early Web applications largely involved simple presentations of data, such as a corporate website displaying personnel information, contact information, and other static information. However, the current trend of Web applications involves a dynamic exchange of data, complicated logic and functionality, animated graphics, and an international focus. As a result, the content and functionality of Web applications are becoming increasingly complex and difficult to manage.

[0003] Given the expanding international scope and complicated nature of Web applications, a need exists for a simple and efficient architecture for providing Web applications with information localized to the target audience.

**BRIEF DESCRIPTION OF THE DRAWINGS**

**[0004]** Advantages of one or more disclosed embodiments may become apparent upon reading the following detailed description and upon reference to the drawings in which:

**[0005]** FIG. 1 is a block diagram that illustrates a model-view-controller (“MVC”) application architecture, which may be created using embodiments of the present invention;

**[0006]** FIG. 2 is a block diagram that illustrates a web presentation architecture in accordance with embodiments of the present invention; and

**[0007]** FIGS. 3 and 4 are block diagrams that illustrate the operation of a web application program created using a web presentation architecture in accordance with embodiments of the present invention.

**DETAILED DESCRIPTION**

**[0008]** One or more specific embodiments of the present invention will be described below. In an effort to provide a concise description of these embodiments, not all features of an actual implementation are described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers’ specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it

should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

**[0009]** FIG. 1 is a block diagram that illustrates a model-view-controller (“MVC”) application architecture, which may be created using embodiments of the present invention. As illustrated, the MVC architecture 10 separates the application object or model 12 from a view 16, which is responsible for receiving an input and presenting an output to a client 14. In a web application context, the client 14 may comprise a browser. The model object and the view are also separated from the control functions of the application, which are represented in FIG. 1 as a controller 18. In general, the model 12 comprises an application state 20, the view 16 comprises presentation logic 22, and the controller 18 comprises control and flow logic 24. By separating these three MVC objects 12, 16, and 18 with abstract boundaries, the MVC architecture 10 may provide flexibility, organization, performance, efficiency, and reuse of data, presentation styles, and logic.

**[0010]** The WPA 100 may be configured with a variety of object-oriented programming languages, such as Java by Sun Microsystems, Inc., Santa Clara, California. An object is generally an item that can be individually selected and manipulated. In object-oriented programming, an object may comprise a self-contained entity having data and procedures to manipulate the data. For example, a Java-based system may utilize a variety of JavaBeans, servlets, Java Server Pages, and so forth. JavaBeans are independent, reusable software modules. In general, JavaBeans support introspection (a builder tool can analyze how a JavaBean works),

customization (developers can customize the appearance and behavior of a JavaBean), events (JavaBeans can communicate), properties (developers can customize and program with JavaBeans), and persistence (customized JavaBeans can be stored and reused). JSPs provide dynamic scripting capabilities that work in tandem with HTML code, separating the page logic from the static elements. According to certain embodiments, the WPA 100 may be designed according to the Java 2 Platform Enterprise Edition (J2EE), which is a platform-independent, Java-centric environment for developing, building and deploying multi-tiered Web-based enterprise applications online.

**[0011]** The model 12 comprises a definitional framework representing the application state 20. For example, in a web-based application, the model 12 may comprise a JavaBean object or other suitable means for representing the application state 20. Regardless of the application or type of object, an exemplary model 12 may comprise specific data and expertise or ability (methods) to get and set the data (by the caller). The model 12 generally focuses on the intrinsic nature of the data and expertise, rather than the extrinsic views and extrinsic actions or business logic to manipulate the data. However, depending on the particular application, the model 12 may or may not contain the business logic along with the application state. For example, a large application having an application tier may place the business logic in the application tier rather than the model objects 12 of the web application, while a small application may simply place the business logic in the model objects 12 of the web application.

**[0012]** As noted above, the view and controller objects 16 and 18 separately address these extrinsic views and actions or business logic. For example, the model 12 may represent data relating to a person (e.g., an address, a birth date, phone number, etc.), yet the model 12 is independent of extrinsic formats (e.g., a date format) for displaying the personal data or extrinsic actions for manipulating the personal data (e.g., changing the address or phone number). Similarly, the model 12 may represent data and expertise to track time (e.g., a clock), yet the model 12 is independent of specific formats for viewing the clock (e.g., analog or digital clock) or specific actions for manipulating the clock (e.g., setting a different time zone). These extrinsic formats and extrinsic actions are simply not relevant to the intrinsic behavior of the model clock object. One slight exception relates to graphical model objects, which inherently represent visually perceptible data. If the model 12 represents a particular graphical object, then the model 12 has expertise to draw itself while remaining independent of extrinsic formats for displaying the graphical object or extrinsic actions for creating or manipulating the graphical object.

**[0013]** The view 16 generally manages the visually perceptible properties and display of data, which may be static or dynamic data derived in whole or in part from one or more model objects 12. As noted above, the presentation logic 22 functions to obtain data from the model 12, format the data for the particular application, and display the formatted data to the client 14. For example, in a web-based application, the view 16 may comprise a Java Server Page (JSP page) or an HTML page having presentation logic 22 to obtain, organize, format, and display static and/or dynamic data. Standard or custom action tags (e.g., `jsp:useJavaBean`) may function to retrieve data dynamically from one or more model objects 12 and insert model data within the

JSP pages. In this manner, the MVC architecture 10 may facilitate multiple different views 16 of the same data and/or different combinations of data stored by one or more model objects 12.

[0014] The controller 18 functions as an intermediary between the client 14 and the model object 12 and view 16 of the application. For example, the controller 18 can manage access by the view 16 to the model 12 and, also, manage notifications and changes of data among objects of the view 16 and objects of the model 12. The control and flow logic 24 of the controller 18 also may be subdivided into model-controllers and view-controllers to address and respond to various control issues of the model 12 and the view 16, respectively. Accordingly, the model-controllers manage the models 12 and communicate with view-controllers, while the view-controllers manage the views 16 and communicate with the model-controllers. Subdivided or not, the controllers 18 ensure communication and consistency between the model 12, the view 16, and the client 14.

[0015] In operation, the control and flow logic 24 of the controller 18 generally receives requests from the client 14, interprets the client requests, identifies the appropriate logic function or action for the client requests, and delegates responsibility of the logic function or action. Requests may be received from the client via a number of protocols, such as Hyper Text Transfer Protocol (“HTTP”) or HTTP with Secure Sockets Layer (“HTTPS”). Depending on the particular scenario, the appropriate logic function or action of the controller 18 may include direct or indirect interaction with the view 16 and/or one or more model objects 12. For example, if the appropriate action involves alteration of extrinsic properties of data

(e.g. reformatting data in the view 16), then the controller 18 may directly interact with the view 16 without the model 12. Alternatively, if the appropriate action involves alteration of intrinsic properties of data (e.g., values of data in the model 12), then the controller 18 may act to update the corresponding data in the model 12 and display the data in the view 16.

**[0016]** FIG. 2 is a block diagram illustrating an exemplary web presentation architecture (“WPA”) 100 in accordance with certain embodiments of the present invention. The illustrated WPA 100, which may be adapted to execute on a processor-based device such as a computer system or the like, has certain core features of the MVC computing strategy, and various additional features and enhancements to improve its architectural operation and performance. For example, the illustrated WPA 100 separates the model, the view, and the controller as with the traditional MVC architecture, yet the WPA 100 provides additional functionality to promote modularity, flexibility, and efficiency.

**[0017]** As illustrated, the WPA 100 comprises a WPA controller 102 having a preprocessor 104, a localization manager 106, the navigation manager 108, a layout manager 110, a cookie manager 112, and object cache manager 114, and a configuration manager 116. The WPA controller 102 functions as an intermediary between the client 14, form objects 118, action classes 120, and views 122. In turn, the action classes 120 act as intermediaries for creating/manipulating model objects 124 and executing WPA logic 126, such as an error manager 128, a performance manager 130, and activity manager 132, and a backend service manager 134. As described below, the backend service manager 134 functions to interface backend



services 136. Once created, the model objects 124 can supply data to the view 122, which can also call various tag libraries 142 such as WPA tag libraries 144 and service tag libraries 146.

**[0018]** In operation, the client 14 sends a request 148 to the WPA 100 for processing and transmission of a suitable response 150 back to the client 14. For example, the request 148 may comprise a data query, data entry, data modification, page navigation, or any other desired transaction. As illustrated, the WPA 100 intakes the request 148 at the WPA controller 102, which is responsible for various control and flow logic among the various model-view-controller divisions of the WPA 100. For example, the WPA controller 102 can be implemented as a Servlet, such as a HyperText Transfer Protocol (“HTTP”) Servlet, which extends the ActionServlet class of Struts (an application framework promulgated by the Jakarta Project of the Apache Software Foundation). As illustrated, the WPA controller 102 invokes a configuration resource file 152, which provides mapping information for form classes, action classes, and other objects. Based on the particular request 148, the WPA controller 102 locates the appropriate action class and, also, the appropriate form class if the request 148 contains form data (e.g., client data input). For example, the WPA controller 102 may lookup a desired WPA Action Form and/or WPA Action Class, which function as interfaces to WPA Form Objects and WPA Action Objects.

**[0019]** If the client entered data, then the WPA controller 102 creates and populates the appropriate form object 118 as indicated by arrow 154. The form object 118 may comprise any suitable data objects type, such as a JavaBean, which

functions to store the client entered data transmitted via the request 148. The WPA controller 102 then regains control as indicated by arrow 156.

**[0020]** If the client did not enter data, or upon creation and population of the appropriate form object 118, then the WPA controller 102 invokes the action class 120 to execute various logic suitable to the request 148 as indicated by arrow 158. For example, the action class 120 may call and execute various business logic or WPA logic 126, as indicated by arrow 160 and discussed in further detail below. The action class 120 then creates or interacts with the model object 124 as indicated by arrow 162. The model object 124 may comprise any suitable data object type, such as a JavaBean, which functions to maintain the application state of certain data. One example of the model object 124 is a shopping cart JavaBean, which stores various user data and e-commerce items selected by the client. However, a wide variety of model objects 124 are within the scope of the WPA 100. After executing the desired logic, the action class 120 forwards control back to the WPA controller 102 as indicated by arrow 164, which may be referred to as an “action forward.” This action forward 164 generally involves transmitting the path or location of the server-side page, e.g., the JSP.

**[0021]** As indicated by arrow 166, the WPA controller 12 then invokes the foregoing server-side page as the view 122. Accordingly, the view 122 interprets its links or tags to retrieve data from the model object 124 as indicated by arrow 168. Although a single model object 124 is illustrated, the view 122 may retrieve data from a wide variety of model objects. In addition, the view 122 interprets any special logic links or tags to invoke tag libraries 142 as indicated by arrow 170. For example,

the WPA tag libraries 144 and the service tag libraries 146 can include various custom or standard logic tag libraries, such as <html>, <logic>, <template> developed as part of the Apache Jakarta Project or the like. Accordingly, the tag libraries 142 further separate the logic from the content of the view 122, thereby facilitating flexibility and modularity. In certain cases, the tag libraries 142 also may interact with the model object 124 as indicated by arrow 172. For example, a special tag may execute logic to retrieve data from the model object 124 and manipulate the retrieved data for use by the view 122. After interacting with the model object 124 and the appropriate tag libraries 142, the WPA 100 executes the view 122 (e.g., JSP) to create a client-side page for the client 14 as indicated by arrow 174. For example, the client-side page may comprise an extended markup language (“XML”) or HTML formatted page, which the WPA controller 102 returns to the client 14 via the response 150.

**[0022]** As discussed above, the WPA 100 comprises a variety of unique logic and functional components, such as control components 104 through 116 and logic 128 through 134, to enhance the performance of the overall architecture and specific features 100. These components and logic generally operate on the server-side of the WPA 100, yet there are certain performance improvements that may be apparent on the client-side. These various components, while illustrated as subcomponents of the controller 102 or types of logic 126, may be standalone or integrated with various other portions of the WPA 100. Accordingly, the illustrated organization of these components is simply one exemplary embodiment of the WPA 100, while other organizational embodiments are within the scope of the present technique.

**[0023]** Turning to the subcomponents of the WPA controller 102, the preprocessor 104 provides preprocessing of requests by configuring portal specific functions to execute for each incoming request registered to the specific portal. The preprocessor 104 identifies the appropriate portal specific functions according to a preset mapping, e.g., a portal-to-function mapping in the configuration file 152. Upon completion, the preprocessor 104 can redirect to a remote Uniform Resource Identifier (URI), forward to a local URI, or return and continue with the normal processing of the request 148 by the WPA controller 102. One example of such a preprocessing function is a locale, which is generally comprised of language preferences, location, and so forth. The preprocessor 104 can preprocess local logic corresponding to a particular portal, thereby presetting language preferences for subsequent pages in a particular application.

**[0024]** The locale information is also used by the localization manager 106, which functions to render localized versions of entire static pages rather than breaking up the static page into many message strings or keys. Instead of using a single page for all languages and obtaining localized strings from other sources at run time, the localization manager 106 looks up a localized page according to a locale identifier according to a preset mapping, e.g., a locale-to-localized page mapping in the configuration file 152. For example, the capability to render static localized pages in the localization manager 106 is particularly useful for static information, such as voluminous help pages.

**[0025]** The navigation manager 108 generally functions to save a users intended destination and subsequently recall that information to redirect the user back

to the intended destination. For example, if the user intends to navigate from point A to point B and point B queries for certain logic at point C (e.g., a user login and password), then the navigation manager 108 saves the address of point B, proceeds to the requested logic at point C, and subsequently redirects the user back to point B.

**[0026]** The layout manager 110 enables a portal to separate the context logic functioning to render the common context from the content logic functioning to render the content portion of the page. The common context (e.g., C-Frame) may include a header, a bottom portion or footer, and a side portion or side bar, which collectively provides the common look and feel and navigational context of the page.

**[0027]** The cookie manager 112 functions to handle multiple cookie requests and to set the cookie value based on the most recent cookie request before committing a response. For example, in scenarios where multiple action classes attempt to set a particular cookie value, the cookie manager 112 caches the various cookie requests and defers setting the cookie value until response time. In this manner, the cookie manager 112 ensures that different action classes do not erase cookie values set by one another and, also, that only one cookie can exist with a particular name, domain, and path.

**[0028]** The object cache manager 114 enables applications to create customized in-memory cache for storing objects having data originating from backend data stores, such as databases or service based frameworks (e.g., Web Services Description Language “WSDL”). The in-memory cache may be customized according to a variety of criteria, such as cache size, cache scope, cache replacement

policy, and time to expire cache objects. In operation, the object cache manager 114 improves performance by reducing processing time associated with the data from the backend data stores. Instead of retrieving the data from the backend data stores for each individual request 148, the object cache manager 114 caches the retrieved data for subsequent use in processing later requests.

[0029] The configuration manager 116 functions to oversee the loading of frequently used information, such as an error code table, into memory at startup time of a particular web application. The configuration manager 116 may retain this information in memory for the duration of an application server session, thereby improving performance by eliminating the need to load the information each time the server receives a request.

[0030] Turning to the WPA logic 126, the error handler or manager 128 functions to track or chain errors occurring in series, catalog error messages based on error codes, and display error messages using an error catalog. The error catalog of the error manager 128 may enable the use of generic error pages, which the error manager 128 populates with the appropriate error message at run time according to the error catalog.

[0031] The WPA logic function 126 may comprise performance and activity managers 130 and 132, which may facilitate tracking and logging of information associated with a particular transaction or request. The error manager 128 may also be adapted to participate in tracking and logging operations as well.

[0032] The service manager 134 of the WPA logic 126 functions as an interface between the WPA 100 and various backend services 136. In operation, the service manager 134 communicates with the desired backend service 136 according to the client request 148, parses a response from the backend service 136 to obtain the appropriate data, and pass it to the appropriate object of WPA 100.

[0033] Turning now to FIGS. 3 and 4, an exemplary localization control process 200 of the localization manager 106 is described according to certain embodiments of the present technique. As noted above with reference to FIG. 2, the localization manager 106 may employ a variety of localization control logic to select a localized page from a plurality of locale-versions of the page, thereby improving the efficiency of creating the pages at development time. For example, the localization manager 106 can identify and recall any number of different locale-versions of a page based on locale parameters, such as language, country, variant, etc. If a user requests a page, then the localization manager 106 simply retrieves the appropriate locale-version of the page for presentation with the Web application. Accordingly, the localization manager 106 internationalizes pages of a Web application in a simple and efficient manner for static pages.

[0034] As noted above, the localization manager 106 identifies and retrieves different locale-versions of a page based on different locale parameters, such as language, country, and variant. For example, each session can have a desired and/or a default locale object (e.g., Java locale object) identifying the correct locale resources to the localization manager 106. As discussed in further detail below, if the desired locale object is missing, then the localization manager 106 can employ

the default locale object. To retrieve or modify the locale object, the action class 120 has getter and setter methods for the locale object, such as set forth below:

Getter Method:

```
getLocale(javax.servlet.http.HttpServletRequest)
```

Setter Method:

```
setLocale(javax.servlet.http.HttpServletRequest, java.util.Locale)
```

Using these getter and setter methods, the locale objects can be retrieved and modified for the WPA 100.

[0035] The localization manager 106 also may utilize a variety of techniques to register and map localized pages in the WPA 100. First, the present technique configures action forwards 164 for localized pages. For example, the localization manager 106 can identify localized pages in the action mapping of the configuration file 152 or within the action class 120. Regarding the former approach, the following is an example of setting the action forward 164 for a localized page in the action class 120:

```
public class MyAction extends WPAAction {
    public ActionForward perform(...) {
        ...
        (1) WPAActionForward af = new
        (2) WPAActionForward("/myservice/jsp/mypage.jsp");
            af.setLocalized(true);
            return (af);
        }
    }
}
```

As set forth above, the provision of “af.setLocalized(true)” indicates that a localized page is available for the specified action forward. Regarding the latter approach, the



following is an example of setting the action forward 164 for a localized page in an action mapping in the configuration file 152:

```
<action
    path="/myservice/myaction"
    name="com.hp.bco.pl.myservice.MyAction">

    <forward name="content"
path="/myservice/jsp/MyactionContent.jsp">
        <set-property name="localized" value="true"/>
    </forward>
    <forward name="error" path="/itrc/jsp/error.jsp"/>
</action>
```

As set forth above, the provision of `<set-property name="localized" value="true"/>` indicates that a localized page is available for the specified action forward.

[0036] Second, the localization manager 106 provides various layout mapping entries for the localized page in a layout mapping file, e.g., layout-mapping.xml. For example, if a particular page has different locale-versions of a navigational framework (e.g., header, footer, sidebar, or C-Frame), then the layout mapping file may include the following layout mapping entries for English and Japanese versions of a “test” page (e.g., JSP Page):

English-version mapping:

```
<layout-mapping path="/wpa/snf2/jsp/test.jsp"
    portal="itrc" layout="itrc" />
```

Japanese-version mapping:

```
<layout-mapping path="/wpa/snf2/jsp/test_ja.jsp"
    portal="itrc" layout="itrc" />
```

Accordingly, the localization manager 106 supports localized layouts or navigational frameworks (e.g., frames) in combination with the core localized pages.

**[0037]** In operation, the localization control process 200 of the localization manager 106 functions to select the appropriate localized page and/or layouts/frames according to the locale objects, the setting of action forwards, and/or the provision of a mapping file, as described above. First, a web application and/or a web browser can set the locale object according to locale information of the client. For example, the web application may query the client for locale information upon entry into a particular portal or page of the web application. The localization manager 106 can then query the locale object for locale information. Second, if the page localized property in the mapping file or configuration file 152 is not set (i.e., not localized), then the WPA 100 utilizes the page path passed into the action forward 164. However, if the page localized property is set to true (i.e., localized), then the localization manager 106 queries for the localized page in the file system.

**[0038]** In either case, the search for the appropriate localized page may proceed in the following order using the present locale parameters:

- (1) <basename> + \_<desired language> + \_<desired country> + \_<desired variant> + .jsp
- (2) <basename> + \_<desired language> + \_<desired country> + .jsp
- (3) <basename> + \_<desired language> + .jsp
- (4) <basename> + \_<default language> + \_<default country> + \_<default variant> + .jsp

- (5) <basename> + \_<default language> + \_<default country> + .jsp
- (6) <basename> + \_<default language> + .properties
- (7) <basename> + .jsp

wherein basename refers to the name of the page (e.g., myJSPpage), default and desired languages can be identified by two letter ISO-639 codes, default and desired countries can be identified by two letter ISO-3166 codes, and default and desired variants further differentiate locales with other suitable codes. For example, a localized JSP page named “myJSPpage\_ja\_JP.jsp” refers to a basename of myJSPpage, a language of Japanese, and a country of Japan. Similarly, the same page having a language of French and a country of Canada is defined as “myJSPpage\_fr\_CA.jsp.”

[0039] As further illustrated in FIG. 2, the localization control process 200 of the localization manager 106 operates to identify an appropriate page (e.g., path for the action forward 164) for a user request 202 obtained by the WPA 100 from a Web application. At query block 204, the localization control process 200 queries whether the path (e.g., action forward 164) is configured as a localized page. For example, as described in detail above, the localization manager 106 can identify localized pages in the action mapping of the configuration file 152 or within the action class 120. If the path is not configured as a localized page, then the localization control process 200 returns the path of a non-localized or default page 206. If the path is configured as a localized page, then the localization control process 200 proceeds to obtain the locale object for the user request (block 208). For example, the process 200 may acquire a

user locale having current user locale information, such as provided by a user locale cookie (e.g., language, country, variant, etc.).

**[0040]** Using the retrieved locale, the localization control process 200 queries whether the language in the user locale is set (block 210). If the user's language is not set, then the localization control process 200 proceeds to a default locale query (block 212). If the language is set in the user locale, then the localization control process 200 queries whether the country in the user locale is set (block 214). If the user's country is not set, then the localization control process 200 queries whether a file with user's language exists (block 216). If a file with the user's language does exist, then the localization control process 200 returns the path of the appropriate localized file and the user's language (block 218). Otherwise, the localization control process 200 proceeds to the default locale query (block 212).

**[0041]** Referring back to query block 214, if the user's country is set, then the localization control process 200 queries whether a variant in the user locale is set (block 220). If the user's variant is not set, then the localization control process 200 queries whether a file with the user's language and country exists (block 222). If a file with the user's language and country does exist, then the localization control process 200 returns the path of the appropriate localized file and the user's language and country (block 224). Otherwise, the localization control process 200 proceeds to the default locale query (block 212).

**[0042]** Referring back to query block 220, if the user's variant is set, then the localization control process 200 queries whether a file with the user's language,

country, and variant exists (block 226). If a file with the user's language, country, and variant does exist, then the localization control process 200 returns the path of the appropriate localized file and the user's language, country, and variant (block 228). Otherwise, the localization control process 200 proceeds to the default locale query (block 212).

[0043] Turning now to FIG. 4, the localization control process 200 continues to identify an appropriate page using a default locale (e.g., default language, country, and/or variant). Continuing from query block 212 of FIG. 2, the localization control process 200 queries whether the language in the default locale is set (block 230). If the language in the default locale is not set, then the localization control process 200 returns the path of a default file (block 232). If the language is set in the default locale, then the localization control process 200 queries whether the country in the default locale is set (block 234). If the country is not set in the default locale, then the localization control process 200 queries whether a file with the default language exists (block 236). If a file with the default language does exist, then the localization control process 200 returns the path of the appropriate file and default language (block 238). Otherwise, the localization control process 200 returns the path of the default file (block 232).

[0044] Referring back to query block 234, if the country is set in the default locale, then the localization control process 200 queries whether a variant in the default locale is set (block 240). If the variant is not set in the default locale, then the localization control process 200 queries whether a file with the default language and default country exists (block 242). If such a file does exist, then the localization

control process 200 returns the path of the appropriate file and the default language and default country (block 244). Otherwise, the localization control process 200 proceeds to the default locale query (block 232).

**[0045]** Referring back to query block 240, if the variant is set in the default locale, then the localization control process 200 queries whether a file with the default language, default country, and default variant exists (block 246). If such a file does exist, then the localization control process 200 returns the path of the appropriate file and the default language, default country, and default variant (block 248). Otherwise, the localization control process 200 proceeds to the default locale query (block 232).

**[0046]** In view of the foregoing, the localization manager 106 can display pages localized according to a variety of current or default locale parameters, such as language, country, and variant (e.g., dialect). In addition, pages having multiple components, such as a header, sidebar, footer, and content (e.g., C-Frame and content), can be presented with mixed locale content, such as English and non-English components. For example, if the user's locale is French, the C-frame is available in French, but the content (JSP page) is unavailable in French, then the localization manager 106 can display the page in mixed languages (e.g., French and English).

**[0047]** While the invention may be susceptible to various modifications and alternative forms, specific embodiments have been shown by way of example in the drawings and will be described in detail herein. However, it should be understood that the invention is not intended to be limited to the particular forms

disclosed. Rather, the invention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the invention as defined by the following appended claims.